

PJ358

**LIGHT, BRIGHT AND
PORTABLE PROJECTOR**
WITH KEYSTONE CORRECTION

Portable and multifunctional.

The ViewSonic® PJ358 XGA projector weighs in at only 1.78kg but DELIVERS POWERFUL PRESENTATIONS WITH NATIVE 1024×768 RESOLUTION AND AN AMAZING 2,200 LUMENS. Professional presenters will appreciate the full feature set including dual RGB inputs and USB storage support that allow you to connect two PCs or PC-Less Presentation. The PJ358 SETS UP EASILY WITH ITS ONE-TOUCH SET UP BUTTON AND DISPLAYS THE PERFECT IMAGE in virtually any setting thanks to digital keystone correction, manual zoom and focus. The included remote control with mouse makes it easy to deliver a dynamic presentation that puts you in the best possible light.



DELIVER BRIGHT, POWERFUL PRESENTATIONS

> **Bright in virtually any setting with 2,200 lumens**

Packs 2,200 lumens in just 1.78kg. It's the bright choice for mobile presenters.

> **Ultimate video source flexibility**

Connect a computer or add a video source for dynamic meetings and presentations.

> **Supports HD signals including 720p and 1080i**

Capable of displaying HDTV signals as well as other video and data sources.*

> **Advanced video features**

Progressive scan and 3:2 pull down for superior video performance.

> **Whisper-mode extends lamp life & low noise 30dB**

Extend the life of your lamp up to 4,000 hours** and reduce noise output.

> **6 default picture mode for different environment usage**

Dynamic, Cinema, Normal, Whiteboard, Board(Black), and Daylight Mode.

> **Keylock and security slot for anti-theft**

Design to avoid a mischief and touching.

> **Off To Go feature**

Allow to unplug projector power cable without traditional turn off procedure.

> **Short Throw Feature**

Projection 60" image at 1.5m



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic® 

the choice of professionals

PJ358

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION

Model No.VS11611



Optional Accessories

- Replacement lamp.....RLC-027

| (a) Screen size (diagonal) | | 4 : 3 screen | | | | | | | |
|----------------------------|-----|-------------------------|------|------|-----|-------------------|------|------|-----|
| | | (b) Projection distance | | | | (c) Screen height | | | |
| inch | m | min. | max. | down | up | min. | max. | down | up |
| 60 | 1.5 | 1.5 | 61 | 1.9 | 73 | 13 | 5 | 78 | 31 |
| 80 | 2.0 | 2.1 | 81 | 2.5 | 97 | 17 | 7 | 105 | 41 |
| 100 | 2.5 | 2.6 | 102 | 3.1 | 122 | 22 | 9 | 131 | 51 |
| 120 | 3.0 | 3.1 | 122 | 3.7 | 147 | 26 | 10 | 157 | 62 |
| 150 | 3.8 | 3.9 | 153 | 4.7 | 183 | 33 | 13 | 196 | 77 |
| 200 | 5.1 | 5.2 | 204 | 6.2 | 245 | 44 | 17 | 261 | 103 |
| 300 | 7.6 | 7.8 | 306 | 9.3 | 368 | 65 | 26 | 392 | 154 |

| (a) Screen size (diagonal) | | 16 : 9 screen | | | | | | | |
|----------------------------|-----|-------------------------|------|------|-----|-------------------|------|------|-----|
| | | (b) Projection distance | | | | (c) Screen height | | | |
| inch | m | min. | max. | down | up | min. | max. | down | up |
| 60 | 1.5 | 1.7 | 66 | 2.0 | 79 | 2 | 1 | 73 | 29 |
| 80 | 2.0 | 2.2 | 88 | 2.7 | 106 | 2 | 1 | 97 | 38 |
| 100 | 2.5 | 2.8 | 111 | 3.4 | 133 | 3 | 1 | 122 | 48 |
| 120 | 3.0 | 3.4 | 133 | 4.1 | 160 | 3 | 1 | 146 | 58 |
| 150 | 3.8 | 4.2 | 166 | 5.1 | 200 | 4 | 2 | 183 | 72 |
| 200 | 5.1 | 5.6 | 222 | 6.8 | 267 | 5 | 2 | 243 | 96 |
| 300 | 7.6 | 8.5 | 334 | 10.2 | 400 | 8 | 3 | 365 | 144 |

| | | |
|-------------------------------|-------------------------|--|
| PROJECTOR | Type | 0.63" (×3) Poly-Si TFT with micro-lens |
| | Pixel Format | 1024×768 XGA |
| | Lens | Manual zoom, manual focus |
| | Zoom Factor | 1.2 |
| | Keystone | Vertical ±30° |
| DISPLAY | Size | 30"-300" (Diagonal) |
| | Throw Distance | 0.9-9.3m |
| | Throw Ratio | 1.3-1.5 |
| | Lamp | 160W |
| | Brightness | 2,200 ANSI lumens |
| | Contrast Ratio | 500:1 |
| | Aspect Ratio | 4:3 (native), 16:9 |
| AUDIO | Speakers | 1 watt×1 |
| INPUT SIGNAL | Computer and Video | RGB analog, NTSC M, NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576i, 720p, 1080i) |
| | Frequency | Fh:31.5-106 KHz ; Fv:56-120 Hz |
| COMPATIBILITY | PC | from VGA up to UXGA (scaled) |
| | Mac | up to SXGA (may require a Mac adapter) |
| CONNECTOR | RGB (input) | 15-pin HD, D-sub cable (×2) |
| | Composite Video (input) | RCA jack (×1) |
| | S-Video (input) | Mini-Din 4-pin (×1) |
| | Audio (input) | RCA jack (×1 set), Stereo mini jack×1 |
| | Audio (output) | Stereo mini jack |
| | USB | Type A for PC-Less Presentation (JPEG, MPEG4, M-JPEG) Type B for mouse control |
| | POWER | Voltage |
| | Consumption | 250W (typ) |
| CONTROLS | Basic | Standby/On, input, menu |
| | Remote | Language, brightness, contrast, gamma, color temperature, color, tint, sharpness, progressive, My Memory, aspect, overscan, V./H. position, H. phase, H. size, auto adjust, color space, component, video format, frame lock, information, V. keystone, auto keystone, whisper, mirror, volume, audio, language, menu position, OSD bright, blank color, start up, My Screen, Pin Lock, My Screen Lock, message, auto search, auto off, lamp time, filter time, service menu, Security, USB storage, Auto on, Auto off |
| OPERATING CONDITION | Temperature | 41°F - 91°F (5°C - 35°C) |
| | Humidity | 10% - 90% (non-condensing) |
| NOISE LEVEL | Normal | 36 dB (typ) |
| | Elo mode | 30 dB (typ) |
| DIMENSIONS (W × D × H) | Physical (mm) | 274mm×59mm×205mm |
| WEIGHT | Net | 1.78 kg (3.9 lbs) |
| | Gross | 4.5 kg (9.9 lbs) |
| REGULATIONS | | UL 60950, C-UL, FCC-B, TUV/GS, CB, CE, C-TICK, NOM |
| PACKAGE CONTENTS | | Projector, power cords, VGA cable, RCA video cable, remote control, AA Batteries, soft case, lens cap, ViewSonic Wizard CD, Quick Start Guide |

Headquarters:

381 Brea Canyon Road,
Walnut, CA 97189, U.S.A.
salesinfo@viewsonic.com
www.viewsonic.com

Asia Pacific:

9F, No. 1 92 Lien Chien Road,
Chung Ho, Taipei, R.O.C.
www.viewsonic.com.tw

ViewSonic Hong Kong

Unit 3, 15/F, Greenfield Tower,
Concordia Plaza,
1 Science Museum Road, TST East,
Kowloon, Hong Kong
www.hk.viewsonic.com

ViewSonic (Singapore) Pte Ltd

Marine Parade Road #09-02
Parkway Parade
Singapore 449269
www.viewsonic.com.sg

ViewSonic Australia Pty Ltd

Unit 3, 44 Dickson Avenue,
Artarmon NSW 2064, Australia
www.viewsonic.com.au

ViewSonic Korea

#907, 9F, Hyundai HYEL, 2-36,
Hangangro 2-ga,
Yongsan-gu, Seoul, Korea 140-871
www.kr.viewsonic.com

ViewSonic Technologies (India) Pvt Ltd.

M-28, Commercial Complex (M-Block Market) 3rd floor,
Greater Kailash-II N Delhi - 110 048, India
in.viewsonic.com

ViewSonic 
the choice of professionals